

MATERIALS & SPECIFICATIONS

INSULATOR:
LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138.

CONTACT:
COPPER ALLOY PER MIL-DTL-83513. GOLD PLATE PER ASTM B488, (HARD GOLD) TYPE II CODE C, CLASS 1.27


TERMINATION:
COPPER ALLOY PER MIL-DTL-83513 GOLD PLATED PER ASTM B488, (HARD GOLD) TYPE II CODE C CLASS 1.27.

CURRENT CAPACITY:
3 AMP MAX.



CONTACT RESISTANCE:
26 MILLIOHMS (65mV) MAX @ 2.5 AMPS.

PERFORMANCE:
PRODUCT FAMILY TESTED TO AND PASSED THE PERFORMANCE SPECIFICATIONS OF TABLE VII OF MIL-DTL-83513.

PART NO.	A22033-001	REV	ECO	DATE	APP
		C	98556	05-18-12	TLM



ACTUAL SIZE



RoHS

MCS SLDW	THIRD ANGLE		THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF OMNETICS CONNECTOR CORP. THIS DOCUMENT MAY NOT, IN WHOLE OR IN PART, BE DUPLICATED, OR DISCLOSED FOR ANY PURPOSE, WITHOUT WRITTEN PERMISSION FROM OMNETICS CONNECTOR CORP.				OMNETICS CONNECTOR CORPORATION 7260 COMMERCE CIRCLE EAST MINNEAPOLIS, MN 55432 WWW.OMNETICS.COM	CAGE CODE 61873	
	-TOLERANCES-							DWG NO.	
	UNLESS OTHERWISE NOTED		A22033-001						
	DIMENSIONS IN INCHES		DFTM. TLM	DATE	TITLE:	(16) SOCKET FEMALE MICRO CIRCULAR CONNECTOR		SHEET 1 OF 1	REV
	2 PL DEC± .01		CHK'D.	DATE	SCALE: 4:1			C	
	3 PL DEC± .005		APP'D.	DATE					
	4 PL DEC± .0005								
	ANGLES ± 1°								