

MATERIALS & SPECIFICATIONS

HOUSING:

ALUMINUM 6061, NICKEL
PLATED (500 MICROINCHES
MINIMUM) PER SAE-AMS-
2404.

INSULATOR:

LIQUID CRYSTAL POLYMER
(LCP) PER ASTM 5138

CONTACT:

BERYLLIUM COPPER PER ASTM
B194, C17200, GOLD PLATED
PER ASTM B488, (HARD
GOLD) TYPE II, CODE C,
CLASS 1.27

TERMINATION:

SOLDER COATED WITH SN63A
PER J-STD-006 OR AMS-P-
81728

HARDWARE:

303 STAINLESS STEEL PER
ASTM A582

CURRENT RATING:



1 AMP MAX PER MIL-DTL-
32139

CONTACT RESISTANCE:



71 MILLIOHM MAX (71mV
DROP MAX) @ 1.0 AMPS PER
MIL-DTL-32139

PERFORMANCE:

PRODUCT FAMILY TESTED TO
AND PASSED THE
PERFORMANCE SPECIFICATIONS
OF TABLE VIII OF MIL-DTL-
32139.



VIEW LESS HARDWARE



SUGGESTED HOLE PATTERN

NOTES:

1. TAIL DIMENSIONS APPLY AT
PLANE A.

2. DIMENSIONS IN [] ARE IN
MILLIMETERS UNLESS
OTHERWISE NOTED AND ARE
FOR REFERENCE ONLY.

MBPS	THIRD ANGLE	
	-TOLERANCES-	
SLDW	UNLESS OTHERWISE NOTED	
	DIMENSIONS IN INCHES	
	2 PL DEC± .01	
	3 PL DEC± .005	
	4 PL DEC± .0005	
	ANGLES ± 1°	

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH IS
THE PROPERTY OF OMNETICS CONNECTOR CORP. THIS DOCUMENT MAY NOT, IN
WHOLE OR IN PART, BE DUPLICATED, OR DISCLOSED FOR ANY PURPOSE,
WITHOUT WRITTEN PERMISSION FROM OMNETICS CONNECTOR CORP.

TITLE:
DFTM. JMJ
DATE
10-11-13

(9) PIN MALE
SINGLE ROW
BI-LOBE® CONNECTOR

OMNETICS
CONNECTOR CORPORATION
8840 EVERGREEN BLVD.
MINNEAPOLIS, MN 55433
WWW.OMNETICS.COM

DWG NO.	CAGE CODE	61873
A50019-009		
SHEET 1 OF 1	SCALE: 3:1	REV E