

MATERIAL & SPECIFICATIONS

HOUSING:
ALUMNIUM 6061-T6,
NICKEL PLATE PER SAE-
AMS-2404.

INSULATOR:
THERMOPLASTIC PER
MIL-DTL-32139.


CONTACT:
BERYLLIUM COPPER PER
ASTM B194, C17200,
GOLD PLATED PER ASTM
B488, (HARD GOLD) TYPE
II CODE C, CLASS 1.27.

WIRE:
NEMA HP3 TYPE ET,
COLOR CODED IAW MIL-
STD-681, SYSTEM 1,
USING TEN SOLID
REPEATING COLORS.


HARDWARE:
303 STAINLESS STEEL
PER ASTM 582.

CURRENT RATING:
1 AMP MAX PER MIL-
DTL-32139.

PERFORMANCE:
PRODUCT FAMILY TESTED
TO AND PASSED THE
PERFORMANCE
SPECIFICATIONS OF TABLE
VIII OF MIL-DTL-32139.



ACTUAL SIZE
EXCLUDING WIRE
LENGTH



PIN #	COLOR
1, 11, 21	BLACK
2, 12	BROWN
3, 13	RED
4, 14	ORANGE
5, 15	YELLOW
6, 16	GREEN
7, 17	BLUE
8, 18	VIOLET
9, 19	GRAY
10, 20	WHITE

NOTE:

DIMENSIONS IN [] ARE IN
MILLIMETERS UNLESS
OTHERWISE NOTED AND ARE
FOR REFERENCE ONLY

MBPS	THIRD ANGLE	
	-TOLERANCES-	
SLDW	UNLESS OTHERWISE NOTED	
	DIMENSIONS IN INCHES	
	2 PL DEC±	.01
	3 PL DEC±	.005
	4 PL DEC±	.0005
	ANGLES ± 1°	

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF OMNETICS CONNECTOR CORP. THIS DOCUMENT MAY NOT, IN WHOLE OR IN PART, BE DUPLICATED, OR DISCLOSED FOR ANY PURPOSE, WITHOUT WRITTEN PERMISSION FROM OMNETICS CONNECTOR CORP.			
DFTM. MJM	DATE	TITLE:	
CHK'D.	03-31-11	(21) PIN MALE	
APP'D.		Bi-Lobe® CONNECTOR	

OMNETICS	
CONNECTOR CORPORATION	
7260 COMMERCE CIRCLE EAST	
MINNEAPOLIS, MN 55432	
WWW.OMNETICS.COM	

CAGE CODE 61873	
DWG NO. A54000-021	
SHEET 1 OF 1	REV G
SCALE: 4:1	