






PART NO.	A79289-001	REV	ECO	DATE	APP
		D	101657	06-02-15	TLM



ACTUAL SIZE
EXCLUDING WIRE LENGTH

PIN #	COLOR
1, 11	BLACK
2	BROWN
3	RED
4	ORANGE
5	YELLOW
6	GREEN
7	BLUE
8	VIOLET
9	GRAY
10	WHITE

INTERNAL USE ONLY
USE MFG LOADING
PROCEDURE NC-11P



IP68

NOTE:
DIMENSIONS IN [] ARE IN
MILLIMETERS UNLESS
OTHERWISE NOTED AND ARE
FOR REFERENCE ONLY

MNC PLDW	THIRD ANGLE
	—TOLERANCES—
	UNLESS OTHERWISE NOTED
	DIMENSIONS IN INCHES
	2 PL DEC $\pm .01$
	3 PL DEC $\pm .005$
	4 PL DEC $\pm .0005$
	ANGLES $\pm ^\circ$

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF OMNETICS CONNECTOR CORP. THIS DOCUMENT MAY NOT, IN WHOLE OR IN PART, BE DUPLICATED, OR DISCLOSED FOR ANY PURPOSE, WITHOUT WRITTEN PERMISSION FROM OMNETICS CONNECTOR CORP.	
DFTM. NJS	DATE 01-20-12
CHK'D.	DATE
APP'D.	DATE
TITLE: (11) PIN MALE NANO THREADED PANEL MOUNT SEALED CIRCULAR CONNECTOR	

OMNETICS

CONNECTOR CORPORATION

7260 COMMERCE CIRCLE EAST
MINNEAPOLIS, MN 55432
WWW.OMNETICS.COM

CAGE CODE 61873	DWG NO. A79289-001
SHEET 1 OF 2	REV D
SCALE: 3:1	

PART NO.	A79289-001	REV	ECO	DATE	APP
		D	101657	06-02-15	TLM

MATERIALS & SPECIFICATIONS

INSULATOR
THERMOPLASTIC PER MIL-M-24519

CONTACT MATERIAL
PINS - BERYLLIUM COPPER PER ASTM B194, ALLOY C17200

CONTACT FINISH
GOLD PLATE PER ASTM B488, TYPE II (HARD GOLD), CODE C,
CLASS 1.27 (.000050)

WIRE
32 AWG, 7 STRAND, TYPE ET PER NEMA HP3

SHELLS
BRASS ALLOY 360

SHELL FINISH
ELECTROLESS NICKEL PER SAE-AMS-2404

O-RING
BUNA-N

CURRENT RATING
1 AMP PER MIL-DTL-32139

CONTACT RESISTANCE
71 MILLIOHM MAX (71mV DROP MAX) @ 1.0 AMPS PER
MIL-DTL-32139

PERFORMANCE
PRODUCT FAMILY TESTED TO AND PASSED THE PERFORMANCE
SPECIFICATIONS OF TABLE VIII OF MIL-DTL-32139

SEALING PERFORMANCE
PRODUCT FAMILY TESTED TO AND PASSED IP68 REQUIREMENTS
WHEN MATED WITH ANOTHER IP68 RATED CONNECTOR

MNC P SLDW	THIRD ANGLE 	THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF OMNETICS CONNECTOR CORP. THIS DOCUMENT MAY NOT, IN WHOLE OR IN PART, BE DUPLICATED, OR DISCLOSED FOR ANY PURPOSE, WITHOUT WRITTEN PERMISSION FROM OMNETICS CONNECTOR CORP.				 OMNETICS CONNECTOR CORPORATION 7260 COMMERCE CIRCLE EAST MINNEAPOLIS, MN 55432 WWW.OMNETICS.COM	CAGE CODE 61873	
	-TOLERANCES-						DWG NO. A79289-001	
	DIMENSIONS IN INCHES						SHEET 2 OF 2	
	2 PL DEC $\pm$.01 3 PL DEC $\pm$.005 4 PL DEC $\pm$.0005 ANGLES $\pm$ °	DFTM. NJS CHK'D. APP'D.	DATE 01-20-12 DATE DATE	TITLE: (11) PIN MALE NANO THREADED PANEL MOUNT SEALED CIRCULAR CONNECTOR	REV D		SCALE: 3:1	