MATERIALS & SPECIFICATIONS

INSULATOR THERMOPLASTIC PER ASTM D5138

CONTACT MATERIAL PINS - BERYLLIUM COPPER PER ASTM B194, ALLOY C17200

SOCKET - COPPER ALLOY PER MIL-DTL-32139

CONTACT FINISH GOLD PLATE PER ASTM B488, TYPE II (HARD GOLD), CODE C, CLASS

WIRE 32 AWG, 7 STRAND, TYPE ET PER NEMA HP3


CURRENT RATING 1 AMP MAX PER MIL-DTL-32139


CONTACT RESISTANCE 71 MILLIOHM MAX (71mV DROP MAX) @ 1.0 AMPS PER MIL-DTL-32139

PERFORMANCE PRODUCT FAMILY TESTED TO AND PASSED THE PERFORMANCE SPECIFICATIONS OF TABLE VIII OF MIL-DTL-32139



ACTUAL SIZE EXCLUDING WIRE LENGTH





A79600-001

REV

 $\Box$ 

ECO

104492

DATE

05-22-18

APP

HV

PART NO.

CONTACT #	COLOR
1	BLACK
2	BROWN
3	RED
4	ORANGE

INTERNAL USE ONLY SHEET 2 OF 2 IS MANUFACTURING LOADING DIAGRAM

[1.78] <del></del>	32 AWG (7-40) PTFE, COLOR CODED
.080 [2.03]	

RoHS

## NOTE:

DIMENSIONS IN [ ] ARE IN MILLIMETERS UNLESS OTHERWISE NOTED AND ARE FOR REFERENCE ONLY

THIRD ANGLE + -TOLERANCES-UNLESS OTHERWISE NOTED DIMENSIONS IN INCHES 2 PL DEC± .01 3 PL DEC± .005 4 PL DEC± .0005 ANGLES ± 1°

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF OMNETICS CONNECTOR CORP. THIS DOCUMENT MAY NOT. IN WHOLE OR IN PART, BE DUPLICATED, OR DISCLOSED FOR ANY PURPOSE, WITHOUT WRITTEN PERMISSION FROM OMNETICS CONNECTOR CORP

DFTM. NJS 08-24-10 CHK'D. APP'D.

(4) CONTACT POLARIZED MALE/FEMALE NANO CONNECTOR


ECTOR CORPORATION A79600-0017260 COMMERCE CIRCLE EAST MINNEAPOLIS, MN 55432 WWW.OMNÉTICS.COM

S CAGE CODE 61873

SHEET 1 OF 2 REV D

SCALE: 10:1

PART NO.	A79600-001	REV	ECO	DATE	APP
		D	104492	05-22-18	HV



CONTACT #	COLOR
1	BLACK
2	BROWN
3	RED
4	ORANGE



THIRD ANGLE⊕ ←	THIS DRAWING CONTAINS CONFIDENTIAL AND	PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF	OMMERICO	CACE CODE 61	072
□ -TOLERANCES-	OMNETICS CONNECTOR CORP. THIS DOCUME	INT MAY NOT, IN WHOLE OR IN PART, BE DUPLICATED, OR	<b>OMNETICS</b>	DWO NO	575
UNLESS OTHERWISE NOTED  DIMENSIONS IN INCHES					
2 PL DEC±.01	DFTM. NJS 08-24-10	(4) CONTACT POLARIZED	CONNECTOR CORPORATION	A79600-0	01
≌  3 PL DEC± .005	CHK'D.	MALE/FEMALE	7260 COMMERCE CIRCLE EAST	SHEET 2 OF 2	REV
4 PL DEC± .0005   ≼ ANGLES ± 1°	APP'D.	NANO CONNECTOR	MINNEAPOLIS, MN 55432 WWW OMNETICS COM	SCALE: 20:1	D