

PART NO.	A79649-001	REV	ECO	DATE	APP
		B	101562	05-08-15	TLM

Technical drawing of a rectangular plate with two rows of holes. The left row contains 10 cross-shaped holes (labeled 22) and the right row contains 10 circular holes (labeled 21). The total height of the plate is .250 [6.35]. The diameter of the circular holes is .040 [1.02]. The pitch between the centers of the holes in each row is .025 [0.64]. The thickness of the plate is .020 [0.51]. The drawing also shows a .025 [0.64] dimension for the vertical spacing between the hole rows and a .020 [0.51] dimension for the plate thickness.

Technical drawing of a component with dimensions in inches and millimeters in brackets. The drawing shows a side view of a component with a central rectangular body and a curved, shaded area on the right side. Dimensions are as follows:

- Top width: $.06$ [1.5]
- Left height: $.300$ [7.62]
- Bottom width: $.170$ [4.32]
- Right side: 11X $\phi .008$, [0.20] SOLDER COATED

REV	DATE	BY	CHKD	APPD
1	10/10/02	SS	SS	TS
2				

PERFORMANCE
PRODUCT FAMILY TESTED TO
AND PASSED THE
PERFORMANCE
SPECIFICATIONS OF TABLE
VIII OF MIL-DTL-32139



Technical drawing of a plate with 14 holes. The drawing includes the following dimensions:

- Overall width: .025 [0.64] TYP
- Overall height: .047 [1.19]
- Distance from top edge to center of first hole: .013 [0.33]
- Distance from bottom edge to center of first hole: .013 [0.33]
- Distance from left edge to center of first hole: .025 [0.64] TYP
- Distance between centers of adjacent holes: .025 [0.64] TYP
- Distance from center of last hole to right edge: .025 [0.64] TYP
- Overall length: .250 [6.35]
- Overall diameter of holes: ϕ .016 [0.41] TYP

16
013
41]
33]
YP

.070
[1.78]

.080
[2.03]

25
64]

DATECODE MARKING
"YYWW" THIS SIDE

.100
[2.54]

11X .008 X .0025
[0.20] X [0.064]
SOLDER COATED

DIMENSIONS IN [] ARE IN
MILLIMETERS UNLESS
OTHERWISE NOTED AND ARE
FOR REFERENCE ONLY

PZN	THIRD ANGLE	THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF OMNETICS CONNECTOR CORP. THIS DOCUMENT MAY NOT, IN WHOLE OR IN PART, BE DUPLICATED, OR DISCLOSED FOR ANY PURPOSE, WITHOUT WRITTEN PERMISSION FROM OMNETICS CONNECTOR CORP.			 CONNECTOR CORPORATION 7260 COMMERCE CIRCLE EAST MINNEAPOLIS, MN 55432 WWW.OMNETICS.COM	CAGE CODE 61873	
	—TOLERANCES—	DFTM. JMJ DATE 04—12—13 TITLE: (22) CONTACT POLARIZED MALE/FEMALE NANO CONNECTOR	DWG NO.	REV B			
	UNLESS OTHERWISE NOTED		A79649—001				
	DIMENSIONS IN INCHES						
SLDW	2 PL DEC ± .01 3 PL DEC ± .005 4 PL DEC ± .0005 ANGLES ± 1°	CHK'D.	APP'D.	SHEET 1 OF 1	SCALE: 8:1		