

PART NO.	A98202-512	REV	ECO	DATE	APP
		Α	103557	06-21-17	TLM

MATERIALS

HOUSING:

ALUMINUM 6061-T6, NICKEL PLATE (500 MICROINCHES MINIMUM) PER SAE-AMS-2404

INSULATOR:

LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138

CONTACT:

BERYLLIUM COPPER PER ASTM B194, C17200, GOLD PLATED PER ASTM B488, (HARD GOLD) TYPE II CÓDE C, CLASS 1.27

WIRE:

NEMA HP3 TYPE E, COLOR CODED IAW MIL-STD-681, SYSTEM 1, USING TEN SOLID REPEATING COLORS

HARDWARF:

AVAILABLE UPON REQUEST

PIN #	COLOR
1, 11, 21, 31, 41, 51	BLACK
2, 12, 22, 32, 42	BROWN
3, 13, 23, 33, 43	RED
4, 14, 24, 34, 44	ORANGE
5, 15, 25, 35, 45	YELLOW
6, 16, 26, 36, 46	GREEN
7, 17, 27, 37, 47	BLUE
8, 18, 28, 38, 48	VIOLET
9, 19, 29, 39, 49	GRAY
10, 20, 30, 40, 50	WHITE

INTERNAL USE ONLY USE MFG LOADING PROCEDURE MMDP-512



Α

THIRD ANGLE

TOLERANCES

UNLESS OTHERWISE NOTED

DIMENSIONS IN INCHES THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF -TOLERANCES-OMNETICS CONNECTOR CORP. THIS DOCUMENT MAY NOT IN WHOLE OR IN PART BE DUPLICATED OR DISCLOSED FOR ANY PURPOSE, WITHOUT WRITTEN PERMISSION FROM OMNETICS CONNECTOR CORP UNLESS OTHERWISE NOTED DFTM. ERB 01-10-17 TITLE: 2 PL DEC± .01 3 PL DEC± .005 4 PL DEC± .0005 ANGLES ± 1° (51) PIN MALE CHK'D. MICRO-D CONNECTOR APP'D.

CAGE CODE 61873 DWG NO. CONNECTOR CORPORATION A98202-512 7260 COMMERCE CIRCLE EAST MINNEAPOLIS, MN 55432

WWW.OMNÉTICS.COM

SHEET 2 OF 2 REV SCALE: 3:1