

A98181-512 APP PART NO. REV ECO DATE A 102791 08-09-16 HV

MATERIALS

HOUSING:

ALUMINUM 6061-T6, NICKEL PLATE PER SAE-AMS-2404

INSULATOR:

LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138

CONTACT:

BERYLLIUM COPPER PER ASTM B194, C17200, GOLD PLATED PER ASTM B488, (HARD GOLD) TYPE II CODE C, CLASS 1.27

WIRE:

NEMA HP3 TYPE E, COLOR CODED IAW MIL-STD-681, SYSTEM 1, USING TEN SOLID REPEATING COLORS

HARDWARF:

STAINLESS STEEL, PASSIVATED PER SAE-AMS-2700

COLOR
BLACK
BROWN
RED
ORANGE
YELLOW
GREEN
BLUE
VIOLET
GRAY
WHITE

INTERNAL USE ONLY USE MFG LOADING PROCEDURE MMDP-512

3	THIRD ANGLE⊕ ← -TOLERANCES-	OMNETICS CONNECTOR	CORP. THIS DOCUMEN	PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF THE MANUAL PROPERTY OF THE MANUAL PROPERTY OF THE PROPERTY OF
JDP ISI DW	UNLESS OTHERWISE NOTED DIMENSIONS IN INCHES 2 PL DEC±.001 3 PL DEC±.0005 4 PL DEC±.0005 ANGLES±1°		DATE DATE DATE DATE DATE	TITLE: (51) PIN MALE MICRO-D CONNECTOR W/ JACKSCREWS

ETICS CAGE CODE 61873 DWG NO. CONNECTOR CORPORATION A98181-512 7260 COMMERCE CIRCLE EAST SHEET 2 OF 2 REV MINNEAPOLIS, MN 55432 WWW.OMNÉTICS.COM

Α SCALE: 3:1